## NSN 5905-01-018-9972

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-018-9972

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.6245 inches
Pilot Length:
Between 0.0570 inches and 0.0570 inches
Undercut Diameter:
0.781 inches
Undercut Width:
0.0670 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.339 inches
Body Length:
1.032 inches
Mounting Lip Diameter:
0.7810 inches
Mounting Lip Depth:
0.0670 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section

-0.010/+0.010 single section

Terminal Type And Quantity:

**Resistance Tolerance Per Section In Percent:** 

3 turret

## NSN 5905-01-018-9972

Precision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

tion:

No

Fiig:

A002a0