NSN 5905-01-019-0288

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-019-0288

-50 0/450 0 Electrical Resistance: 16 500 kilohoms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire laad Reliability Indicator: Not established Terminal Length: Between 0.094 inches and 0.165 inches Body Length: Between 0.094 inches and 0.165 inches Body Length: Between 0.093 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Between 0.023 inches and 0.027 inches Terminal Width: Between 0.023 inches and 0.027 inches Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bach1/4u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure: Demilitarization: No Filig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 16.900 kilohms Resistance Tolerance in Percent: -0.1004/-0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Langth: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.093 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: B1205-bacch14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
16.900 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.375 inches and 1.625 inches Body Diameter: Bottween 0.094 inches and 0.165 inches Body Length: Between 0.094 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bach14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Filig:	
-0.100/4-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.394 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: Between 1.023 inches and 0.027 inches Test Data Document: Setween 1.023 inches and 0.027 inches Test Data Document: Setween 0.023 inches and 0.027 inches Test Data Document: Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.343 inches and 0.165 inches Body Length: Between 0.343 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: Between 0.023 inches and 0.027 inches Test Data Document: Setween 1.023 inches and 0.027 inches Test Data Document: Setween 0.023 inches and 0.027 inches Test Data Document: Unit Off Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/415.00 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.093 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: Between 0.023 inches and 0.027 inches Test Data Document: Step Data Document: Step Data Document: Step Data Document: Unit Of Measure: Demilitarization: No Flig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: B1205-bacrh1u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.394 inches and 0.165 inches Body Dength: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bach14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Diameter: Between 0.094 inches and 0.437 inches Bedween 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-56.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	150.0
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Botween 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encased
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 1.375 inches and 1.625 inches
Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.094 inches and 0.165 inches
Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.313 inches and 0.437 inches
Terminal Width: Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Between 0.023 inches and 0.027 inches Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 free air
Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Width:
81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.023 inches and 0.027 inches
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0