## NSN 5905-01-019-0296

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-019-0296

Electrical Resistance: 130.000 ohms Resistance Tolerance in Percent: -0.500/40.05 ohms Resistance Tolerance in Percent: -0.500/40.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 180.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Length: Between 0.031 inches and 0.165 inches Body Length: Between 0.031 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Alia terminal each end Test Data Document: 81 205-5bach1-fu drewing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit of Measure: - Demilitarization: No Filig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 130.000 ohms Resistance Tolerance In Percent: -0.500/40.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4150.0 Inclosure Method: Encased Terminal Type: Wire lead Realiability Indicator: Not established Terminal Length: Between 0.395 inches and 1.625 inches Body Dlameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.393 inches and 0.437 inches Power Dissipation Rating In Watts: -0.125 froe air Terminal Width: Between 0.032 inches and 0.027 inches Style Designator: Avail terminal each end Test Data Document: B1205-bacnth 4u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Lite: Na Unit Of Measure: Demilitarization: No Filig:	
Resistance Tolerance in Percent: -0.500/4-0.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.934 inches and 0.165 inches Body Diameter: Between 0.313 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Yudit: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Note Chemitatization: No Pilig:	
Resistance Tolerance in Percent: -0.500/40.500 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.313 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: 81205-Bacthi Hu drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: Na Unit of Measure:	
-0.500/40.500 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire laad Reliability Indicator: Not established Terminal Length: Between 1,375 inches and 1,625 inches Body Diameter: Between 0,313 inches and 0,1625 inches Body Length: Between 0,313 inches and 0,437 inches Power Dissipation Rating In Watts: 0,125 free air Terminal Width: Between 0,023 inches and 0,027 inches Style Designator: Akial terminal each end Test Data Document: B1205-bach14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,375 inches and 1.625 inches Body Diameter: Between 0,094 inches and 0.165 inches Body Length: Between 0,031 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0,023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: B1205-bacth/Hu drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1,375 inches and 1.625 inches Body Diameter: Between 1,375 inches and 0.165 inches Body Length: Between 0,094 inches and 0.165 inches Body Length: Between 0,313 inches and 0.437 inches Power Dissipation Rating In Watts: 0,125 free air Terminal Width: Between 0,231 inches and 0.027 inches Style Designator: Avial terminal each end Test Data Document: Bl205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0  Inclosure Method: Encased  Terminal Type: Wire laed Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches Body Jameter: Between 0.94 inches and 0.165 inches Body Jameter: Between 0.94 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air  Terminal Width: Between 0.231 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: Bational Test Data Document: Style Designator: Axial terminal each end Test Data Document: Unit Off Measure:  Via Unit Off Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0.4 15.0.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.75 in inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.094 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: B1205-bach14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: - Demilitarization: No Filg:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Dameter: Between 0.341 inches and 0.165 inches Body Length: Between 0.343 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: 81205-bach14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
-5.0/+150.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Diameter: Between 0.094 inches and 0.457 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Aikali terminal each end Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.376 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating In Watts: 0.125 free air Terminal Width: Between 0.23 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: Unit Of Mea	
Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.094 inches and 0.437 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: 81205-bacth14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Body Length: Between 0.313 inches and 0.437 inches Power Dissipation Rating in Watts: 0.125 free air Terminal Width: Between 0.023 inches and 0.027 inches Style Designator: Axial terminal each end Test Data Document: B1205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fiig:	
Wire lead  Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.165 inches  Body Length: Between 0.094 inches and 0.437 inches  Body Length: Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width: Between 0.023 inches and 0.027 inches  Style Designator: Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	
Reliability Indicator: Not established  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.165 inches  Body Length: Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width: Between 0.023 inches and 0.027 inches  Style Designator: Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	
Note stablished  Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.165 inches  Body Length: Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width: Between 0.023 inches and 0.027 inches  Style Designator: Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Filg:	
Terminal Length: Between 1.375 inches and 1.625 inches  Body Diameter: Between 0.094 inches and 0.165 inches  Body Length: Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width: Between 0.023 inches and 0.027 inches  Style Designator: Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No Fig:	
Between 1.375 inches and 1.625 inches  Body Diameter:  Between 0.094 inches and 0.165 inches  Body Length:  Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts:  0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Between 0.094 inches and 0.165 inches  Body Length:  Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	
Between 0.094 inches and 0.165 inches  Body Length:  Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fig:	
Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Between 0.313 inches and 0.437 inches  Power Dissipation Rating In Watts: 0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Power Dissipation Rating In Watts:  0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
0.125 free air  Terminal Width:  Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Filig:	
Between 0.023 inches and 0.027 inches  Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
Style Designator:  Axial terminal each end  Test Data Document:  81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Terminal Width:
Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Between 0.023 inches and 0.027 inches
Axial terminal each end  Test Data Document: 81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Style Designator:
81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
excludes any specification, standard or other document that may be referenced in a basic governing drawing)  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Test Data Document:
Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	81205-bacrh14u drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization:  No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0