NSN 5905-01-019-1203

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-019-1203 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.3120 inches and 1.3125 inches Pilot Length: 0.0620 inches **Overall Length:** 1.593 inches **Undercut Diameter:** 1.31300 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 1.468 inches **Shaft Diameter:** Between 0.2494 inches and 0.250 inches **Shaft Length:** 0.500 inches **Body Length:** 1.062 inches **Overall Diameter:** 1.828 inches **Mounting Lip Diameter:** 1.4370 inches **Mounting Lip Depth:** 0.0930 inches **Effective Electrical Rotation In Deg Angular Rotation:**

Shaft Style: Round **Actuator Type:** Single shaft 350.0 **Maximum Running Torque:** 0.75 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches

NSN 5905-01-019-1203

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 turret
Specification Data:

N/a

Shelf Life:

Unit Of Measure:

81349-mil-r-12934/19 government specification

NSN 5905-01-019-1203

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0