Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-019-3658

Section	Quantity:	

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

**Overall Length:** 

0.353 inches

Terminal Length:

0.125 inches

Body Diameter:

0.395 inches

Body Length:

0.228 inches

**Overall Diameter:** 

0.395 inches

Actuator Type:

Flush drive with slot-hole

## Effective Electrical Rotation In Deg Angular Rotation:

270.0

## Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

#### Mounting Method:

Terminal

#### Features Provided:

Humidity proof

**Electrical Resistance Per Section:** 

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

270.0

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+150.0 single section

## **Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# NSN 5905-01-019-3658

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0