

View Online at <https://aerobasegroup.com/nsn/5905-01-019-3674>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.281 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.562 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Overall Diameter:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Nonturn Device Location:

At 4'30 oclock and at 10'30 oclock

Nonturn Device Radius:

0.245 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

300.0 ohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+4.5 -55 degrees celsius single section and +0.0/+2.5 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section and -1.5/+1.5 85 degrees celsius single section and +0.0/+3.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0