Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-019-8439
Section Quantity:
1
Reliability Indicator:
Not established
Overall Length:
4.984 inches
Overall Height:
4.750 inches
Overall Width:
3.812 inches
Switch Type:
Rotary
Contact Arm Electrical Off Position:
Fully ccw
Actuator Type:
Integral knob with counter
Effective Electrical Rotation In Deg Angular Rotation:
3604.0
Switch Operating Position:
End of linear movement
Terminal Location:
Upper adjacent side single row
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
6.9 free air single section
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Continuous motion
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-130.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Unit can be used as a rheostat

## NSN 5905-01-019-8439

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0