Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-019-8442

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.147 inches

#### **Body Diameter:**

0.938 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.694 inches

#### Mounting Bushing Length:

## 0.375 inches

**Body Length:** 

0.453 inches

#### **Overall Diameter:**

1.258 inches

## Shaft Style:

Round, slotted, knurled

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.438 inches

#### Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

5.0 megohms single section

# NSN 5905-01-019-8442

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg: 7200.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

---

Fiig:

A002a0