NSN 5905-01-020-2388

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-020-2388

view Offilite at https://aerobasegroup.com/nsn/0303-01-020-2300
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-90.0/+90.0
Electrical Resistance:
0.010 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Heat Sink Material:
Aluminum alloy
Heat Sink Length:
12.000 inches
Heat Sink Width:
12.000 inches
Heat Sink Thickness:
0.059 inches
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Inclosure Method: Encased
Encased
Encased Terminal Type:
Encased Terminal Type: Tab, solder lug
Encased Terminal Type: Tab, solder lug Reliability Indicator:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts:
Encased Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.406 inches Body Length: 1.968 inches Body Width: 0.630 inches Body Height: 0.610 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 1.563 inches Power Dissipation Rating In Watts: 20.000 free air

0.125 inches

NSN 5905-01-020-2388

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Style Designator:
Axial terminal (s)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A001a0