NSN 5905-01-020-2428

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-020-2428 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.812 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.000 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 3610.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 96.00 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:**

0.002 inches

Pilot Diameter Runout:

0.005 inches

NSN 5905-01-020-2428

Precision Wire Wound Variable Resistor - Page 2 of 3



Objets Destinal Plans
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Shaft seal
Electrical Resistance Per Section:
70.0 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary at 10'30 oclock
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 all sections
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
6 oclock all primaries
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a

NSN 5905-01-020-2428

Precision Wire Wound Variable Resistor - Page 3 of 3



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A002a0