## NSN 5905-01-020-3194

**Fiig:** A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-020-3194

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| -10.0/+10.0  |
| Electrical Resistance:   |
| 680.000 kilohms  |
| Resistance Tolerance In Percent:   |
| -0.100/+0.100  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 145.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -65.0/+145.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.500 inches   |
| Body Length:   |
| 1.000 inches   |
| Power Dissipation Rating In Watts:   |
| 0.750 free air   |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-milr39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain        |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                          |
| Specification Data:  |
| 81349-mil-r-39005/7a government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |