NSN 5905-01-020-3212

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-020-3212

Section Quantity:
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.378 inches
Terminal Length:
0.188 inches
Body Diameter:
0.375 inches
Body Length:
0.200 inches
Overall Diameter:
0.375 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
180.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
· · · · · · · · · · · · · · · · · · ·
•

NSN 5905-01-020-3212

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0