

View Online at <https://aerobasegroup.com/nsn/5905-01-020-7136>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.609 inches

Body Diameter:

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.281 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.312 inches

Overall Diameter:

1.484 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Undercut Length:

0.531 inches

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

20.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

50.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

350.0

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0