Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-020-9332

## Section Quantity:

1

Body Style:

Rectangular

## Reliability Indicator:

Not established

#### **Terminal Length:**

0.188 inches

#### Shaft Diameter:

0.090 inches

#### Shaft Length:

0.062 inches

#### Body Length:

0.416 inches

#### Body Width:

0.200 inches

## Body Height:

0.375 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Terminal

#### **Features Provided:**

Humidity proof

#### **Electrical Resistance Per Section:**

25.0 kilohms single section

## Rotary Actuator Travel In Angular Deg:

7200.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

#### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# NSN 5905-01-020-9332 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.5 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

#### Fiig:

A002a0