Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-021-6822

•	•
Section	Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.312 inches

**Body Length:** 

0.406 inches

**Body Width:** 

0.312 inches

**Body Height:** 

0.300 inches

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Lower adjacent side single row

#### Mounting Method:

Terminal

# **Features Provided:**

Hermetically sealed

#### **Electrical Resistance Per Section:**

25.0 kilohms single section

# **Rotary Actuator Travel In Angular Deg:**

1440.0

### Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

# Actuator Travel Control Feature:

Clutch



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0