Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-022-3546

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# **Reliability Indicator:**

Not established

## **Overall Length:**

0.472 inches

#### **Terminal Length:**

0.172 inches

#### **Overall Height:**

0.250 inches

#### Overall Width:

0.165 inches

#### Shaft Diameter:

0.075 inches

# Shaft Length:

0.050 inches

# Body Length:

0.250 inches

# Body Width:

0.165 inches

#### Body Height:

0.250 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 9000.0

#### Maximum Running Torque:

3.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Rear end

# **Mounting Method:**

Terminal

# Center To Center Distance Between Terminal Rows:

0.100 inches

## **Features Provided:**

Nonmetallic shaft

# NSN 5905-01-022-3546

---

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Electrical Resistance Per Section:** 200.000 ohms single section **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.250 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22097/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0