NSN 5905-01-022-6443

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-022-6443

| · |
|---|
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 0.562 inches |
| Terminal Length: |
| 0.188 inches |
| Overall Height: |
| 0.766 inches |
| Overall Width: |
| 0.510 inches |
| Body Length: |
| 0.562 inches |
| Body Width: |
| 0.510 inches |
| Body Height: |
| 0.598 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 295.0 |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Lower adjacent side two rows |
| Mounting Method: |
| Terminal |
| Center To Center Distance Between Terminal Rows: |
| 0.200 inches |
| Electrical Resistance Per Section: |
| 25.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 295.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| |

NSN 5905-01-022-6443

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Resistance Tolerance Per Section In Percent: |
|---|
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |