

View Online at <https://aerobasegroup.com/nsn/5905-01-022-6446>

**Section Quantity:**

1

**Body Style:**

Rectangular w/pointer adjustment

**Reliability Indicator:**

Not established

**Terminal Length:**

0.125 inches

**Body Length:**

0.625 inches

**Body Width:**

0.625 inches

**Body Height:**

0.510 inches

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

295.0

**Maximum Starting Torque:**

6.00 inch-ounces

**Maximum Running Torque:**

6.00 inch-ounces

**Mechanical Backlash In Deg Angular Rotation:**

3.0

**Center To Center Distance Between Terminals:**

0.200 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

0.200 inches

**Features Provided:**

Shaft seal

**Cubic Measure:**

0.199 cubic inches

**Electrical Resistance Per Section:**

1.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

295.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.100 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

U single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0