NSN 5905-01-022-9608

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-022-9608

| Section Quantity: |
|---|
| Section Quantity: |
| |
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 4.094 inches |
| First Flat Length: |
| 1.562 inches |
| Flat Height: |
| 0.344 inches |
| Body Diameter: |
| 5.000 inches |
| Shaft Diameter: |
| 0.375 inches |
| Shaft Length: |
| 2.000 inches |
| Body Length: |
| 2.094 inches |
| Overall Diameter: |
| 5.438 inches |
| Shaft Style: |
| Round, flatted |
| Contact Arm Electrical Off Position: |
| Fully ccw |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 310.0 |
| Screw Thread Diameter: |
| 0.250 inches |
| Screw Thread Series Designator: |
| Unc |
| Screw Thready Qty Per Inch (tpi): |
| 20.0 |
| Mounting Facility Quantity: |
| 2 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |

Threaded hole

NSN 5905-01-022-9608

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Electrical Resistance Per Section: |
|---|
| 13.0 ohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 310.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 340.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 225.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 2 tab w/screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |