NSN 5905-01-023-5829

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-023-5829

Section Overtitus
Section Quantity:
Body Style:
Cylindrical Polichility Indicators
Reliability Indicator:
Not established
Overall Length:
0.500 inches
Terminal Length:
0.250 inches
Body Diameter:
0.300 inches
Body Length:
0.250 inches
Overall Diameter:
0.300 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
1440.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
500.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

NSN 5905-01-023-5829

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0