

View Online at <https://aerobasegroup.com/nsn/5905-01-023-7574>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

35.0 millimeters

**Body Diameter:**

Between 22.0 millimeters and 25.5 millimeters

**Shaft Diameter:**

Between 5.9 millimeters and 6.0 millimeters

**Shaft Length:**

Between 8.5 millimeters and 11.5 millimeters

**Mounting Bushing Length:**

9.525 millimeters

**Body Length:**

15.0 millimeters

**Overall Diameter:**

34.0 millimeters

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

354.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

Between 9.6 millimeters and 10.4 millimeters

**Screw Thread Diameter:**

9.525 millimeters

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.25/+0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

70.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.4 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0