## NSN 5905-01-024-0376

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-024-0376
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-250.0/+250.0 second temp coefficient
Electrical Resistance:
3.920 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
+0.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Diameter:
Between 0.030 inches and 0.070 inches
Body Length:
Between 0.660 inches and 0.785 inches
Body Width:
0.310 inches
Body Height:
0.200 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
1.500 total network
Terminal Width:

Between 0.014 inches and 0.024 inches

### **Identical Value Resistor Quantity:**

3 lowest resistance value3 highest resistance value1 1st intermediate resistance value1 2nd intermediate resistance value1 3rd intermediate resistance value

#### **Style Designator:**

**Dual inline** 

#### **Test Data Document:**

87990-755090a0031 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# NSN 5905-01-024-0376

Film Fixed Resistor Network - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0