NSN 5905-01-024-0810

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-024-0810

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Overall Length:
1.060 inches
Terminal Length:
0.200 inches
Overall Height:
0.560 inches
Overall Width:
0.280 inches
Mounting Hole Diameter:
0.088 inches
Shaft Diameter:
0.100 inches
Shaft Length:
0.060 inches
Body Length:
1.000 inches
Body Width:
0.280 inches
Body Height:
0.360 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.500 inches
Fragility Factor:
Moderately delicate
Lateral Distance Between Mounting Hole Centers:
0.830 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Unthreaded hole and terminal

NSN 5905-01-024-0810

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.200 inches
Electrical Resistance Per Section:
100.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig:

A002a0