NSN 5905-01-024-4112

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-024-4112

Section Quantity:				
1				
Body Style:				
Rectangular				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
0.100				
Terminal Length:				
0.300 inches				
Shaft Diameter:				
0.075 inches				
Shaft Length:				
0.080 inches				
Body Length:				
0.375 inches				
Body Width:				
0.170 inches				
Body Height:				
0.375 inches				
Shaft Style:				
Round, slotted				
Actuator Type:				
Single shaft				
Effective Electrical Rotation In Deg Angular Rotation:				
Between 5400.0 and 10800.0				
Center To Center Distance Between Terminals:				
0.200 inches				
Terminal Location:				
Left adjacent side two rows				
Mounting Method:				
Terminal				
Center To Center Distance Between Terminal Rows:				
0.100 inches				
Features Provided:				
Humidity proof				
Electrical Resistance Per Section:				
5.0 kilohms single section				
Rotary Actuator Travel In Angular Deg:				
Between 5400.0 and 10800.0				
Center To Center Distance Between Center Terminal And Outside Terminal:				

0.100 inches

NSN 5905-01-024-4112

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature	In Deg Celsius Pe	r Section At Zero	Percent Rated Power:
---------------------	-------------------	-------------------	-----------------------------

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/2 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0