NSN 5905-01-024-4119

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-024-4119
Section Quantity:
1
Body Style:
Rectangular w/mounting holes
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Mounting Hole Diameter:
Between 0.073 inches and 0.083 inches
Shaft Diameter:
Between 0.065 inches and 0.095 inches
Shaft Length:
Between 0.025 inches and 0.045 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.210 inches and 0.230 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
7920.0
Center To Center Distance Between Terminals:
0.200 inches
Lateral Distance Between Mounting Hole Centers:
Between 0.515 inches and 0.530 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole and terminal
Electrical Resistance Per Section:
50.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-01-024-4119

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: