

View Online at <https://aerobasegroup.com/nsn/5905-01-024-9103>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.813 inches

Mounting Bushing Length:

0.313 inches

Body Length:

1.000 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Shaft End Play:

0.010 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.003 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.20/+0.20 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0