NSN 5905-01-024-9112

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-024-9112

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.997 inches
Terminal Length:
0.540 inches
Body Diameter:
0.500 inches
Body Length:
0.457 inches
Overall Diameter:
0.500 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.200 inches
Electrical Resistance Per Section:
10.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Terror materials Designation Per Continue At Zone Bennant Bated Bennan
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
175.0 single section
175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section
175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section Power Dissipation Rating Per Section In Watts:
175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section Power Dissipation Rating Per Section In Watts: 1.0 free air single section

125.0 single section

NSN 5905-01-024-9112

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0