NSN 5905-01-025-4785

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-025-4785

Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.165 inches
Shaft Diameter:
0.095 inches
Shaft Length:
0.060 inches
Body Length:
0.750 inches
Body Width:
0.190 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
5400.0
Center To Center Distance Between Terminals:
0.500 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100 0/±100 0 single section

0.75 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-01-025-4785

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No