NSN 5905-01-025-6653

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-025-6653 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Overall Length:** 0.472 inches **Terminal Length:** 0.172 inches **Overall Height:** 0.250 inches **Overall Width:** 0.165 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.050 inches **Body Length:** 0.250 inches **Body Width:** 0.165 inches **Body Height:** 0.250 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 9000.0 **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches

Features Provided:

Nonmetallic shaft

NSN 5905-01-025-6653

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.250 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: