

View Online at <https://aerobasegroup.com/nsn/5905-01-025-6948>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.735 mils and 0.765 centimeters

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.859 inches and 0.891 inches

Mounting Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 0.220 inches and 0.280 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 245.0 and 255.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

80.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.370 inches and 0.380 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

0.110 cubic inches

Electrical Resistance Per Section:

1.0 gallons per minute c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 275.0 and 285.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 eyelet

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0