## NSN 5905-01-026-1593

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-026-1593 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Overall Length:** 2.982 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.482 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 357.0 and 359.0 **Maximum Starting Torque:** 2.10 inch-ounces **Maximum Running Torque:** 1.80 inch-ounces **Nonturn Device Location:** At 3 oclock **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.0005 inches **Lateral Runout:** 0.004 inches **Pilot Diameter Runout:** 

0.00200 inches

Shaft Radial Play:

0.004 inches

## NSN 5905-01-026-1593

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better industrial clears
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 2nd section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 2nd section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Features:
Ternimal q type 3
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0