

View Online at <https://aerobasegroup.com/nsn/5905-01-026-2134>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Overall Length:

1.563 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.313 inches

Body Width:

0.266 inches

Body Height:

0.406 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

7920.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Screw Thread Diameter:

0.190 inches

Screw Thread Series Designator:

Unf

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Cubic Measure:

0.142 cubic inches

Electrical Resistance Per Section:

20.0 ohms c and better flooring

Rotary Actuator Travel In Angular Deg:

7920.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0