NSN 5905-01-026-3281

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-026-3281

Section Quantity: 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.378 inches **Terminal Length:** 0.188 inches **Overall Height:** 0.610 inches **Overall Width:** 0.530 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.080 inches **Body Length:** 0.190 inches **Body Width:** 0.530 inches **Body Height:** 0.530 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Left adjacent side single row **Mounting Method: Terminal Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:**

Rotary Actuator Travel In Angular Deg:

1.000 kilohms single section

9000.0

NSN 5905-01-026-3281

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**