NSN 5905-01-026-6248

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-026-6248

| Tompurature Coefficient Of Resistance In Pom Per Dog Colsius | | | | | | |
|--|--|--|--|--|--|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: | | | | | | |
| -50.0/+50.0 Electrical Resistance: | | | | | | |
| 7.970 ohms | | | | | | |
| Resistance Tolerance In Percent: | | | | | | |
| | | | | | | |
| -0.100/+0.100 | | | | | | |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 | | | | | | |
| | | | | | | |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: | | | | | | |
| 275.0 | | | | | | |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 | | | | | | |
| Inclosure Method: | | | | | | |
| | | | | | | |
| Encased Towning Types | | | | | | |
| Terminal Type: | | | | | | |
| Tab, solder lug | | | | | | |
| Reliability Indicator: | | | | | | |
| Not established | | | | | | |
| Terminal Length: | | | | | | |
| 0.438 inches | | | | | | |
| Body Length: | | | | | | |
| 1.062 inches | | | | | | |
| Body Width: | | | | | | |
| 0.550 inches | | | | | | |
| Body Height: | | | | | | |
| 0.546 inches | | | | | | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: | | | | | | |
| 0.719 inches | | | | | | |
| Power Dissipation Rating In Watts: | | | | | | |
| 25.000 free air | | | | | | |
| Terminal Width: | | | | | | |
| 0.140 inches | | | | | | |
| Mounting Hole Size: | | | | | | |
| 0.125 inches | | | | | | |
| Cubic Measure (non-core): | | | | | | |
| 0.319 cubic inches | | | | | | |
| Unpackaged Unit Weight: | | | | | | |
| 16.5 grams | | | | | | |
| Style Designator: | | | | | | |
| Axial terminal (s) | | | | | | |
| Shelf Life: | | | | | | |

N/a

NSN 5905-01-026-6248

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A001a0