NSN 5905-01-026-8464

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-026-8464

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -5.04-5.0 first temp coefficient Electrical Resistance: -5.000 kilohms Resistance Tolerance In Percent: -0.050/4-0.050 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Tempurature Type: | Tanananatura Cartificiani Of Basistana In Bura Bas Bas Calaina |
|--|--|
| Electrical Resistance: 5.000 kilomis Resistance Tolerance in Percent: -0.505/4-0.505 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Tempurature Method: Inclosure Method | |
| Sool kilohms Resistance Tolerance In Percent: -0.050/40.050 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Full Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -56.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 temp range of first temp coefficient In Deg Celsius: -58.0/+125.0 te | |
| Resistance Tolerance in Percent: -0.050/+0.050 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range of first temp coefficient in Deg Celsius: -55.0/+125.0 temp range | |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0/+125.0 temp range of first temp coefficient In Deg Celsius: -57.0 | |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating in Watts: 0.300 riee air Style Designator: Terminals one edge Test Data Document: 81349-mili55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formart, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). | |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 fee air Style Designator: Terminals one edge Test Data Document: 81349-mili55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). | |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient Inclosure Method: Encapsulated Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Length: 0.320 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milit55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Length: 0.320 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milif55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 temp range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Body Height: 0.110 inches Body Height: 0.110 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| -55.0/+125.0 tempr range of first temp coefficient Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 175.0 |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "e. etc.). | Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | -55.0/+125.0 temp range of first temp coefficient |
| Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Inclosure Method: |
| Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milt/55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Encapsulated |
| Reliability Indicator: Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Terminal Type: |
| Established Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Wire lead |
| Reliability Failure Rate Level In Percent: 1.000 Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Reliability Indicator: |
| Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Established |
| Terminal Length: 1.375 inches Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Reliability Failure Rate Level In Percent: |
| Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 1.000 |
| Body Length: 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Terminal Length: |
| 0.310 inches Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 1.375 inches |
| Body Width: 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Body Length: |
| 0.320 inches Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 0.310 inches |
| Body Height: 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Body Width: |
| 0.110 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 0.320 inches |
| Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Body Height: |
| O.300 free air Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 0.110 inches |
| Style Designator: Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Power Dissipation Rating In Watts: |
| Terminals one edge Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 0.300 free air |
| Test Data Document: 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Style Designator: |
| 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Terminals one edge |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | Test Data Document: |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | 81349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| | |
| | Specification Data: |
| 81349-mil-r-55182/9b government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

No

Demilitarization:

NSN 5905-01-026-8464

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0