Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-027-3548

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.411 inches

Flat Height:

0.250 inches

Body Diameter:

1.250 inches

Shaft Diameter:

0.375 inches

Shaft Length:

1.036 inches

Mounting Bushing Length:

0.469 inches

Body Length:

1.500 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

325.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

4.00 inch-ounces

Maximum Stop Torque:

10.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.437 inches

Mechanical Backlash In Deg Angular Rotation:

0.2

Fragility Factor:

Moderately rugged

32.0

N/a

No Fiig:



Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Shaft seal **Electrical Resistance Per Section:** 5.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** 330.0 **Function Conformity Tolerance Per Section:** -0.30/+0.30 all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 all sections **Power Dissipation Rating Per Section In Watts:** 1.0 free air all sections **Function Conformity Per Section:** All sections absolute linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 all sections **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** All sections equation Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections **Test Data Document:** 06481-914103 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 6 turret Shelf Life: Unit Of Measure: **Demilitarization:** A002a0