Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-027-3676

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.938 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.891 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.828 inches

Shaft Style:

Round

Switch Type:

Push-pull

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Switch

NSN 5905-01-027-3676

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -30.0/+30.0 single section Switch Current Type And Rating In Amps: 3.000 ac **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0