## NSN 5905-01-027-8077



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-027-8077 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.250 inches **Body Diameter:** 0.300 inches **Body Length:** 0.250 inches

**Actuator Type:** 

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:** 

1440.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Lower adjacent side single row

**Mounting Method:** 

**Terminal** 

**Electrical Resistance Per Section:** 

20.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

1440.0

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

## NSN 5905-01-027-8077

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0