Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-027-8308

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes

# Reliability Indicator:

Not established

#### **Terminal Length:**

0.500 inches

#### Mounting Hole Diameter:

0.078 inches

#### Shaft Diameter:

0.075 inches

Shaft Length:

0.035 inches

#### Body Length:

### 0.500 inches

Body Width:

0.220 inches

Body Height:

0.500 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Center To Center Distance Between Terminals:

0.200 inches

#### **Fragility Factor:**

Moderately delicate

#### Lateral Distance Between Mounting Hole Centers:

0.520 inches

#### **Mounting Facility Quantity:**

2

# Terminal Location:

Left adjacent side two rows

# Mounting Method:

Terminal and unthreaded hole

# Center To Center Distance Between Terminal Rows:

0.100 inches

# Features Provided:

Humidity proof

# NSN 5905-01-027-8308

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -50.0/+50.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A002a0