NSN 5905-01-028-0163

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-028-0163

-1.0/+1.0 Electrical Resistance: 1.430 kilohms Resistance Tolerance In Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 4.00/+8.00 Inclosure Method: Hermetically seated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Length: 0.438 inches Body Diameter: 0.438 inches Power Dissipation Rating in Watts: 0.391003-2478s-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
1.430 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Diameter: 0.438 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Na Unit Of Measure:	-1.0/+1.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+6.00 Inclosure Method: +dermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Avial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure:	Electrical Resistance:
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-co304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	1.430 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.3300 free air Style Designator: Axial terminal each end Test Data Document: style Test Agravas-co304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 10.0/460.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Diameter: 0.438 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-2473s-0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.390 free air Style Designator: Axial terminal each end Test Data Document: 30003-2473s-03304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+0.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: +0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
+0.0/+60.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	125.0
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	+0.0/+60.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed
Reliability Indicator: Not established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note established Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
2.000 inches Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Diameter: 0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
0.438 inches Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.000 inches
Body Length: 0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
0.812 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.438 inches
Power Dissipation Rating In Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
0.300 free air Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.812 inches
Style Designator: Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.300 free air
Test Data Document: 30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	30003-247as-c0304 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0