NSN 5905-01-028-6416

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-028-6416 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 0.692 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.375 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.250 inches **Overall Diameter:** 0.531 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 32.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.187 inches **Fragility Factor:** Moderately rugged

Screw Thread Diameter: 0.250 inches

NSN 5905-01-028-6416

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Panel seal and shaft seal
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
135.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
-20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret Shelf Life:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret Shelf Life: N/a
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret Shelf Life: N/a
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure:
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section Special Features: Pot hook mtg device Precious Material And Location: Terminals gold and terminals silver Precious Material: Gold and silver Terminal Type And Quantity: 3 turret Shelf Life: N/a Unit Of Measure: Demilitarization: