## NSN 5905-01-028-9150

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-028-9150 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.594 inches **Body Length:** 0.275 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 250.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method: Terminal Electrical Resistance Per Section:** 25.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5905-01-028-9150

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_			٠.								
n	Δ	m	ш	11	o r	17	9	H	^	n	
_	ㄷ		•	IL	aı.	14	а	LI	u		

No

Fiig:

A002a0