NSN 5905-01-029-9873

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-029-9873 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.411 inches Flat Height: 0.220 inches **Body Diameter:** 1.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.036 inches **Mounting Bushing Length:** 0.407 inches **Body Length:** 1.000 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 325.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 4.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.437 inches Mechanical Backlash In Deg Angular Rotation: 0.2 **Fragility Factor:** Moderately rugged **Screw Thread Diameter:**

0.375 inches

Screw Thread Series Designator:

Unef

NSN 5905-01-029-9873

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Panel seal and shaft seal
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
330.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-1.0/+1.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
06481-914102 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0