Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-030-0628

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### Mounting Hole Diameter:

0.088 inches

#### Shaft Diameter:

0.110 inches

#### Shaft Length:

0.080 inches

#### Body Length:

1.260 inches

#### Body Width:

0.190 inches

# Body Height:

0.330 inches

# Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

Between 6190.0 and 9720.0

#### **Fragility Factor:**

Moderately delicate

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

## **Terminal Location:**

Rear end

## **Mounting Method:**

Unthreaded hole

# **Electrical Resistance Per Section:**

500.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

Between 6190.0 and 9720.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Power Dissipation Rating Per Section In Watts:

0.75 free air single section



#### **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

#### Actuator Travel Control Feature:

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0