NSN 5905-01-031-4560

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-031-4560

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.688 inches
Mounting Bushing Length:
0.281 inches
Body Length:
1.300 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
5400.0
Maximum Starting Torque:
0.60 inch-ounces
Maximum Running Torque:
0.60 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Shaft Radial Play:
0.003 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:

Standard bushing

NSN 5905-01-031-4560

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-200.0/+200.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0