Precision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-032-4864

Section Quantity:	
Reliability Indicator:	
Not established	
Actuator Type:	
Flush drive with slot-hole	
Effective Electrical Rotation In Deg Angular Rotation:	
340.0	
Maximum Starting Torque:	
0.60 inch-ounces	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
20.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
-0.50/+0.50 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Pow	ver:
80.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:	
-15.0/+15.0 single section	
Power Dissipation Rating Per Section In Watts:	
4.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Stops	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
25.0 single section	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A002a0	