NSN 5905-01-032-7599

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-032-7599

| Continu Overstitus |
|---|
| Section Quantity: |
| 1 |
| Body Style: |
| Rectangular |
| Terminal Length: |
| 0.300 inches |
| Shaft Diameter: |
| 0.075 inches |
| Shaft Length: |
| 0.080 inches |
| Body Length: |
| 0.375 inches |
| Body Width: |
| 0.170 inches |
| Body Height: |
| 0.375 inches |
| Shaft Style: |
| Round, slotted |
| Shaft Bearing Type: |
| Bearing |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 5400.0 |
| Maximum Starting Torque: |
| 5.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 20.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 360.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |

150.0 single section

NSN 5905-01-032-7599

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Tempurature | Coefficient | Of Resistance | Per Section I | n Ppm Per | Deg Celsius: |
|--------------------|-------------|---------------|---------------|-----------|--------------|
|--------------------|-------------|---------------|---------------|-----------|--------------|

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.500 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 pin

Specification Data:

81349-mil-r-39035/2 government specification

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A002a0