Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-032-7713

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

**Electrical Resistance:** 

2.430 kilohms

**Resistance Tolerance In Percent:** 

-1.000 to 1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

# 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 150.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

**Reliability Failure Rate Level In Percent:** 

0.010

**Terminal Length:** 

Between 1.000 inches and 1.625 inches

#### **Body Diameter:**

Between 0.082 inches and 0.098 inches

## **Body Length:**

Between 0.204 inches and 0.300 inches

**Power Dissipation Rating In Watts:** 

0.250 free air

Unpackaged Unit Weight:

0.5 grams

#### Style Designator:

Axial terminal each end

#### Test Data Document:

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39017/1 government specification

Shelf Life:

N/a

# NSN 5905-01-032-7713

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

