## NSN 5905-01-032-7740

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-032-7740

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
0.500 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.115 inches
Shaft Length:
0.058 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.315 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 6120.0 and 9720.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches

**Electrical Resistance Per Section:** 100.0 kilohms single section

## NSN 5905-01-032-7740

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular D	eg:
Between 6120.0 and 9720.0	

**Center To Center Distance Between Center Terminal And Outside Terminal:** 

0.300 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.75 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Test Data Document:** 

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 pin

**Specification Data:** 

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0