## NSN 5905-01-033-7876

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-033-7876

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.281 inches
Flat Height:
0.107 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.312 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.125 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
50.000 percent, rated amperes c and better industrial clears
Power Dissipation Rating Per Section In Watts:
0.2 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Terminal Type And Quantity:

6 turret

## NSN 5905-01-033-7876

Precision Wire Wound Variable Resistor - Page 2 of 2



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0